

### SAFETY DATA SHEET

THICKENED BLEACH

Page 1 Issued: 17.04.2008

Revision No: 3

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** THICKENED BLEACH

Company name:

Licensed Trade Supplies

13 Dakota Business Park

14 Downley Road

Havant

Hampshire

PO<sub>9</sub> 2NJ

023 9249 9070

info@licensedtrade.net

## 2. HAZARDS IDENTIFICATION

Main hazards: Contact with acids liberates toxic gas. Irritating to eyes and skin.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

**Hazardous ingredients:** MIRYSTYL DIMETHYLAMINE OXIDE 1-5%

CAS: 3332-27-2

[Xi] R41; [Xi] R38

• 1445050 1-5%

CAS: 68585-34-2

[Xi] R36/38

SODIUM HYPOCHLORITE SOLUTION CL ACTIVE 5-10%

EINECS: 231-668-3 CAS: 7681-52-9

[-] R31; [C] R34; [N] R50

### 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause

coughing or wheezing.

# 4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

Issued: 17.04.2008

#### SAFETY DATA SHEET

#### THICKENED BLEACH

Page 2

Ingestion: Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool

containers.

**Exposure hazards:** In combustion emits toxic fumes.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin

and eyes.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking

containers leak-side up to prevent the escape of liquid.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by

an appropriate method.

## 7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do

not handle in a confined space. Avoid the formation or spread of mists in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colourless

Odour: Characteristic odour

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Viscosity: Viscous

Flash point°C: 70

#### Issued: 17.04.2008

## **SAFETY DATA SHEET**

THICKENED BLEACH

Page 3

# 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

**Haz. decomp. products:** In combustion emits toxic fumes.

# 11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: MIRYSTYL DIMETHYLAMINE OXIDE

ORL RAT LD50 > 2000 mg/kg

• 1445050

ORL RAT LD50 > 2000 mg/kg

SODIUM HYPOCHLORITE SOLUTION...100% CL ACTIVE

ORL MUS LD50 5800 mg/kg

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

### 12. ECOLOGICAL INFORMATION

**Hazardous ingredients:** MIRYSTYL DIMETHYLAMINE OXIDE

FISH 96H LC50 10-100 mg/l

**Mobility:** Readily absorbed into soil.

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Negligible ecotoxicity.

## 13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

## 14. TRANSPORT INFORMATION

# ADR / RID

**UN no:** 1791 **ADR Class:** 8

Packing group: III Classification code: C9

Shipping name: HYPOCHLORITE SOLUTION

Labelling: 8 Hazard ID no: 80



#### Issued: 17.04.2008

## **SAFETY DATA SHEET**

THICKENED BLEACH

Page 4

IMDG / IMO

UN no: 1791 Class: 8

Packing group: III EmS: 8-08

Marine pollutant: NO

Labelling: 8

IATA / ICAO

UN no: 1791 Class: 8

Packing group: III

**Packing instructions:** 809(P&CA); 821(PAO)

Labelling: 8

### 15. REGULATORY INFORMATION

Hazard symbols: Irritant.



Risk phrases: R31: Contact with acids liberates toxic gas.

R36/38: Irritating to eyes and skin.

**Safety phrases:** S14: Keep away from other chemicals

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

Note: The regulatory information given above only indicates the principal regulations specifically

applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all

applicable national, international and local regulations or provisions.

### 16. OTHER INFORMATION

**Risk phrases used in s.3:** R41: Risk of serious damage to eyes.

R38: Irritating to skin.

R36/38: Irritating to eyes and skin.

R31: Contact with acids liberates toxic gas.

R34: Causes burns.

R50: Very toxic to aquatic organisms.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall

be used only as a guide. This company shall not be held liable for any damage resulting from

handling or from contact with the above product.